



SECTION 1 - IDENTIFICATION

Manufacturer:

Black Swan Mfg. Co.
4540 W. Thomas St.
Chicago, IL 60651-3318
Tel.: 800-252-5796
Fax: 773-227-3705
Web Site : www.blackswanmfg.com
E-mail : info@blackswanmfg.com

For any Transportation or Medical Chemical Emergencies call:

INFOTRAC(800) 535-5053 **OR** (352) 323-3500

24 hours per day - 7 days a week

Product Name: Dagger**Recommended Use:** For removal of lime, scale, concrete and rust from air conditioning equipment, refrigerator drains, etc.

SECTION 2 – HAZARD(S) IDENTIFICATION

Labels

Irritant Corrosive

Signal Word

Danger

HMIS

HEALTH	3
FLAMMABILITY	0
REACTIVITY	1

NFPA**HEALTH HAZARD**

4 – Deadly
3 – Extreme Danger
2 – Hazardous
1 – Slight Hazardous
0 – Normal Material

SPECIFIC HAZARD

Oxidizer OX
Acid ACID
Alkali ALK
Corrosive COR
Use NO WATER
Radioactive

**FIRE HAZARD**

Flash Points
4 – Below 73°F
3 – Below 100°F
2 – Above 100°F, Not exceeding 200°F
1 – Above 200°F
0 – Will not burn

REACTIVITY

4 – May detonate
3 – Shock and heat may detonate
2 – Violent chemical change
1 – Unstable if heated
0 – Stable

GHS Classification**Health**

Acute Toxicity: Cat.4
Skin Irritation: Cat.1
Eye Irritation: Cat.2B
Skin Sensitization: NO

Environmental

Acute Aquatic Toxicity: Not Established
Chronic Aquatic Toxicity: Not Established

Physical

None

Hazardous Statements

H290: May be corrosive to metals
H304: May be fatal if swallowed and enters airways.
H314: Causes severe skin burns and eye damage
H335: May cause respiratory irritation

Precautionary Statements

P102: Keep out of reach of children
P261: Avoid breathing fume/gas/mist/vapors/spray
P262: Do not get in eyes, on skin, or on clothing
P264: Wash thoroughly after handling
P280: Wear protective gloves/protective clothing/eye protection/face protection

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals**CAS#****EINECS#****REACH****Approx %**

HYDROCHLORIC ACID

7647-01-0

231-595-7

Pre-registration Number

N/A

31-37%

*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

SECTION 4 – FIRST-AID MEASURES

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical attention.**Skin:** Take off contaminated clothing and wash before reuse. Rinse skin with water/shower. Get immediate medical attention.**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so, continue rinsing. Get immediate medical attention.**Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs keep head low so that stomach content does not get into lungs.

GHS SAFETY DATA SHEET

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazard: Contact with common metals may produce flammable and potentially explosive hydrogen gas.
Combustion Products: None known.
Extinguishing Media: Water fog, Foam, Dry Chemical, Carbon Dioxide
Unsuitable Extinguishing Media: Do not use jet water as an extinguisher, as it will spread the fire.
Protective Equipment: Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}. Full protective gear.
Special Fire Fighting Procedures: Firefighters and others who might be exposed to products of combustion should wear (NIOSH approved) positive pressure self-contained breathing apparatus and full protective clothing. Neutralize with soda ash and slake lime.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary personnel from entering the spill area.
Protective Equipment: Wear appropriate protective equipment and clothing during clean-up.
Emergency Procedures: None.
Environmental Precautions: Avoid runoff into storm sewers, ditches and waterways.
Methods for Cleaning Up: Evacuate area; keep upwind until gas has dispersed. If necessary to enter spill area, wear approved full face respirators with acid cartridges. Wear acid resistant clothing. Large Spills: Wear self-contained breathing apparatus and full protective clothing including shoes. Build a dike around the spill. Absorb spillage with non-combustible material such as vermiculite, sand or earth. Take soaked up product and place into a container for later disposal. Clean and dispose in accordance with Federal, State and Local regulations.

SECTION 7 – HANDLING AND STORAGE

<u>Handling</u>	<u>Storage</u>
Do not get in eyes, on skin or on clothing. Avoid breathing vapors or mists. Wash thoroughly after handling. Do not mix with cyanides, sulfides or formaldehyde.	Store in original containers and away from heat. Keep containers closed when not in use. Store in a cool place. Keep away from heat, sparks and flames. Incompatible Materials: Strong oxidizers such as liquid chlorine, sodium or calcium hypochloride, pure oxygen, reducing agents, metals, bases, aldehydes, epoxides, explosives, acetylides, borides, carbides, silicides, cyanides, sulfides and phosphides.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Hazardous Chemicals</u>	<u>ACGIH-TLV</u>	<u>Exposure Limits</u> <u>ACGIH-STEL</u>	<u>OSHA-PEL</u>
HYDROCHLORIC ACID	5 ppm	N/A	5 ppm

Engineering Controls: A source of running water to flush or wash the eyes and skin in case of contact.
Ventilation: Local ventilation is adequate.
Personal Protective Equipment – Respiratory: Full face respirator with HCL fumes cartridge for response to small spills. Self-contained breathing apparatus.
Personal Protective Equipment – Skin: Rubber/Plastic Gloves.
Personal Protective Equipment – Eyes: Chemical safety goggles, safety glasses or face shield.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Light Yellow	Flash Point:	Not Established	Vapor Pressure:	35
Odor:	Pungent/acid odor	Specific Gravity:	1.16	Flammability:	Not Established
pH:	>1	Solubility (H2O):	Complete	Flammability Limits:	LEL – Not Established
Melting Point:	Not Established	Evaporation Rate:	> 1.0		UEL – Not Established
Freezing Point:	Not Established	Vapor Density:	1.17		
Boiling Point:	181°F	VOC:	0 g/l		

GHS SAFETY DATA SHEET

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Conditions to avoid: Open flames, sparks, and ignition sources. Very corrosive to most metals. Avoid heating to decomposition.

Incompatible materials: Strong oxidizers such as liquid chlorine, sodium or calcium hypochloride, pure oxygen, reducing agents, metals, bases, aldehydes, epoxides, explosives, acetylides, borides, carbides, silicides, cyanides, sulfides and phosphides.

Hazardous decomposition products: Carbon monoxide, oxides or sulfur and other decomposition products may form from incomplete combustion. Heat can cause evolution of gaseous hydrogen chloride.

SECTION 11 – TOXICOLOGICAL INFORMATION

<u>Hazardous Chemicals</u>	<u>LD₅₀</u>	<u>Toxicity</u>	<u>LC₅₀</u>
HYDROCHLORIC ACID	Oral: 900 mg/kg (rabbit)	Inhalation: 5,666 ppm @ 30 min.	

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact and Ingestion.

Symptoms and Effect - Inhalation: Corrosive and irritating to respiratory tract. Results in coughing, choking and inflammation of the respiratory tract.

Skin Contact: Will cause severe burns unless washed off immediately. Repeated skin contact may lead to dermatitis.

Eye Contact: Causes severe irritation and painful burns to the eyes and eye lids. Failure to irrigate the eyes immediately with copious amounts of water could cause visual impairment and/or total loss of vision.

Ingestion: Corrosive to mouth and stomach. Do not induce vomiting.

Long-Term Effect: Prolonged exposure to low level concentration of hydrochloric acid vapor may cause discoloration and erosion of teeth, bleeding of nose and gums, and ulcers of the nasal mucosa. It may aggravate asthma, bronchitis, emphysema, bronchial hyperactivity, skin allergies and eczema.

Pre-Existing Conditions: None known.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: This material is expected to be toxic to aquatic life.

Persistence & Degradability: None known.

Bioaccumulative Potential: None known.

Mobility in soil: In normal use, emission of Volatile Organic Compounds (VOC's) to the air takes place, typically at a rate of ≤ 0 g/l.

SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

Shipping Information

Shipping Name: Hydrochloric Acid, Solution
Hazardous Class: 8
I.D. Number: UN1789
Packing Group: II
Label Required: Corrosive
Marine Pollutant: No

Exception to the rule: If the package that contains the hazardous material is in a small consumer size (Less than 1L), then the rules that apply to shipping hazardous materials do not apply. This is called an "Exception".

This is classified as Limited Quantity.

SECTION 15 – REGULATORY INFORMATION

Precautionary Label Information: Health Hazard, Corrosive, Environmental Hazard, Toxic

Risk Phrases: R22-Harmful if swallowed. R35-Causes severe burns. R41-Risk of serious damage to eyes.

Safety Phrases: S2-Keep out of reach of children. S9-Keep container in a well-ventilated place. S25-Avoid contact with eyes. S26-In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2025