



SECTION 1 - IDENTIFICATION

Manufacturer:

Black Swan Mfg. Co.
4540 W. Thomas St.
Chicago, IL 60651-3318
Tel.: 800-252-5796
Fax: 773-227-3705
Web Site : www.blackswanmfg.com
E-mail : info@blackswanmfg.com


For any Transportation or Medical Chemical Emergencies call:

INFOTRAC(800) 535-5053 **OR** (352) 323-3500

24 hours per day - 7 days a week

Product Name: Impact**Recommended Use:** Dissolves grease in drains, grease traps, septic tanks, cess-pools, and dry wells.

SECTION 2 – HAZARD(S) IDENTIFICATION


Labels**Signal Word**
Warning**HMIS**

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

NFPA**HEALTH HAZARD**

4 – Deadly
3 – Extreme Danger
2 – Hazardous
1 – Slight Hazardous
0 – Normal Material

SPECIFIC HAZARD
Oxidizer OX
Acid ACID
Alkali ALK
Corrosive COR
Use NO WATER W
Radioactive R

**FIRE HAZARD**

Flash Points
4 – Below 73°F
3 – Below 100°F
2 – Above 100°F, Not exceeding 200°F
1 – Above 200°F
0 – Will not burn

REACTIVITY
4 – May detonate
3 – Shock and heat may detonate
2 – Violent chemical change
1 – Unstable if heated
0 – Stable

GHS Classification**Health**

Acute Toxicity: Not Established
Skin Irritation: Not Established
Eye Irritation: Cat. 2
Skin Sensitization: NO

Environmental

Acute Aquatic Toxicity: Not Established
Chronic Aquatic Toxicity: Not Established

Physical

Flammable Liquid: Cat. 3

Hazardous Statements

H226: Flammable liquid and vapour
H319: Causes serious eye irritation

Precautionary Statements

P210: Keep away from heat/sparks/open flame/hot surfaces – no smoking
P233: Keep container tightly closed
P242: Use only non-sparking tools
P243: Take precautionary measures against static discharge
P264: Wash thoroughly after handling
P271: Use only outdoors or in a well-ventilated area
P280: Wear protective gloves/protective clothing/eye protection/face protection

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals	CAS#	EINECS#	REACH Pre-registration Number	Approx %
TERPENE HYDROCARBONS	5989-27-5	N/A	N/A	10-25%
ALKANOLAMIDE	68603-42-9	N/A	N/A	10-25%
2-(2-BUTOXYETHOXY) ETHANOL	112-34-5	N/A	N/A	2.5-10%
TETRAPOTASSIUM PYROPHOSPHATE	7320-34-5	N/A	N/A	1-2.5%
ETHANOLAMINES, 2,2'- IMINOBISETHANOL	111-42-2	N/A	N/A	1-2.5%

*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

GHS SAFETY DATA SHEET

SECTION 4 – FIRST-AID MEASURES

Inhalation: Remove victim to fresh air. Provide oxygen if breathing is difficult. Give artificial respiration if the victim is not breathing. Get immediate medical attention.

Skin: Immediately flush skin with water. Take off contaminated clothing and wash before reuse. Get immediate medical attention.

Eyes: Do not rub eyes. Immediately flush eyes with water for at least 15 minutes while holding eyelids open. Remove contact lenses if present and easy to do so, continue rinsing. Get immediate medical attention.

Ingestion: Do not induce vomiting. Get immediate medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazard: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture.

Combustion Products: None known.

Extinguishing Media: Water Fog, Foam, Dry Chemical, Carbon Dioxide.

Unsuitable Extinguishing Media: None known.

Protective Equipment: Wear a self-contained breathing apparatus & protective clothing.

Special Fire Fighting Procedures: Combustible. Clear fire area of unprotected personnel. Do not enter confined fire spaces without helmet, face shield, bunker coat, gloves, rubber boots, and a positive-pressure NIOSH-approved self-contained breathing apparatus.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate the area and keep unnecessary and unprotected personnel from entering the spill area.

Protective Equipment: Wear appropriate personal protective equipment.

Emergency Procedures: None.

Environmental Precautions: Eliminate all ignition sources. Keep product out of sewers and waterways. Do not walk through spilled material. This product is believed not to be dangerous to the environment.

Methods for Cleaning Up: Large Spills: Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage or salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solution as above. Small Spills: Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

SECTION 7 – HANDLING AND STORAGE

Handling

Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. Do not smoke while using this product. Avoid breathing vapour, fumes or mist. Avoid contact with eyes, skin and clothing. Potential peroxide former. If peroxide formation is suspected, do not open or move container. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measure against static discharge. After opening, purge container with nitrogen before reclosing. Addition of water or appropriate reducing materials will lessen peroxide formation. Follow all MSDS/label precautions even after containers are emptied because they may retain product residue.

Storage

Keep container tightly closed. Keep away from heat, sparks and flame. Store container in a cool well ventilated place. Keep from freezing. Keep containers closed when not in use. **Incompatible Materials:** Oxidizing materials, strong acids, lead, copper and their alloys, aluminum, amines, polyamines and nitrosating agents.

GHS SAFETY DATA SHEET

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous Chemicals	Exposure Limits		
	ACGIH-TLV	ACGIH-STEL	OSHA-PEL
TERPENE HYDROCARBONS	N/A	N/A	N/A
ALKANOLAMIDE	N/A	N/A	N/A
2-(2-BUTOXYETHOXY) ETHANOL	10 ppm	N/A	N/A
TETRAPOTASSIUM PYROPHOSPHATE	N/A	N/A	N/A
ETHANOLAMINES, 2,2'- IMINOBISETHANOL	2 mg/m ³	N/A	15 mg/m ³

Engineering Controls: A source of running water to flush or wash the eyes and skin in case of contact.
Ventilation: Use ventilation as required to control vapor concentrations-at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH-approved respirator.
Personal Protective Equipment – Respiratory: NIOSH-approved respirator. **Skin:** Rubber/Plastic gloves. **Eyes:** Safety glasses/splash shield.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Colorless	Flash Point:	130°F	Vapor Pressure:	Not Established
Odor:	Strong Fragrant	Specific Gravity:	Not Established	Flammability:	Not Established
pH:	Not Established	Solubility (H₂O):	Soluble	Flammability Limits:	LEL – Not Established
Melting Point:	Not Established	Evaporation Rate:	<1.0		UEL – Not Established
Freezing Point:	Not Established	Vapor Density:	Not Established		
Boiling Point:	212°F	VOC:	300 g/l		

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.
Hazardous polymerization: Will not occur.
Conditions to avoid: Open flames, sparks, and ignition sources.
Incompatible materials: Oxidizing materials, strong acids, lead, copper and their alloys, aluminum, amines, polyamines and nitrosating agents.
Hazardous decomposition products: Oxides and compounds of nitrogen, carbon dioxide, carbon monoxide and unidentified organic compounds may be formed during combustion.

GHS SAFETY DATA SHEET

SECTION 11 – TOXICOLOGICAL INFORMATION

Hazardous Chemicals	<u>Toxicity</u>	
	<u>LD₅₀</u>	<u>LC₅₀</u>
TERPENE HYDROCARBONS	Oral: 4400 mg/kg Dermal: 5000 mg/kg	N/A
2-(2-BUTOXYETHOXY) ETHANOL	Oral: <1746 mg/kg Dermal: <20000 mg/kg	Vapour: <699.2 mg/kg
ETHANOLAMINES, 2,2'- IMINOBISETHANOL	Oral: <680 mg/kg Dermal: <8180 mg/kg	Vapour: <20 mg/kg

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact, Ingestion

Symptoms and Effect – Inhalation: Vapors/Mists corrosive to the nose, throat, respiratory tract, and other mucous membranes. Overexposure may result in chemical pneumonitis or pulmonary edema which are potentially fatal. Exposure to high concentrations of vapors may produce central nervous system depression. Respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. **Skin Contact:** May be moderately irritating to the skin. Prolonged contact may cause damage to the skin. Prolonged contact may result in defatting and drying of the skin which may result in dermatitis. Skin irritation may include reddening, swelling, rash and redness. **Eye Contact:** Severe irritation to the eyes. May cause extensive corneal injury. Eye irritation may include pain, tearing, reddening and swelling. **Ingestion:** May cause chemical burns to the gastrointestinal tract. May cause kidney damage. May cause liver damage. May cause central nervous system depression.

Long-Term Effect: Symptoms of chronic overexposure include loss of memory, loss of intellectual ability and loss of coordination. Lung sensitization results in asthma-like symptoms: chest-tightness, shortness of breath, wheezing & coughing. These symptoms may be immediate or delayed up to several hours.

Pre-Existing Conditions: Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to this product. Impaired liver functions from pre-existing disorders may be aggravated by exposure to this product.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: None known.

Persistence & Degradability: None known.

Bioaccumulative Potential: None known.

Mobility in soil: In normal use, emission of Volatile Organic Compounds (VOC's) to the air takes place, typically at a rate of 300 g/l.

SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

D.O.T. (U.S.): Not Regulated.

SECTION 15 – REGULATORY INFORMATION

Precautionary Label Information: None.

Risk Phrases: None.

Safety Phrases: S2-Keep out of reach of children.

SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2025