



SECTION 1 - IDENTIFICATION

Manufacturer:

Black Swan Mfg. Co.
4540 W. Thomas St.
Chicago, IL 60651-3318
Tel.: 800-252-5796
Fax: 773-227-3705
Web Site : www.blackswanmfg.com
E-mail : info@blackswanmfg.com

For any Transportation or Medical Chemical Emergencies call:

INFOTRAC(800) 535-5053 **OR** (352) 323-3500

24 hours per day - 7 days a week

Product Name: Pipe Stick**Recommended Use:** Pipe Joint Compound in stick form for sealing threaded pipe on metal or plastic connections.

SECTION 2 – HAZARD(S) IDENTIFICATION

Labels

None

Signal Word

None

HMIS

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0

NFPA**HEALTH HAZARD**

4 – Deadly
3 – Extreme Danger
2 – Hazardous
1 – Slight Hazardous
0 – Normal Material

SPECIFIC HAZARD

Oxidizer
Acid
Alkali
Corrosive
Use NO WATER
Radioactive

**FIRE HAZARD**

Flash Points
4 – Below 73°F
3 – Below 100°F
2 – Above 100°F, Not exceeding 200°F
1 – Above 200°F
0 – Will not burn

REACTIVITY

4 – May detonate
3 – Shock and heat may detonate
2 – Violent chemical change
1 – Unstable if heated
0 – Stable

GHS Classification**Health**

Acute Toxicity: Not Established
Skin Irritation: Not Established
Eye Irritation: Not Established
Skin Sensitization: NO

Environmental

Acute Aquatic Toxicity: Not Established
Chronic Aquatic Toxicity: Not Established

Physical

None

Hazardous Statements

None

Precautionary Statements

P102 : Keep out of reach of children

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals**CAS#****EINECS#****REACH
Pre-registration Number****Approx %**

LINSEED OIL, POLYMERIZED	67746-08-1	N/A	N/A	10-15%
NAPHTHETIC ACIDS, COBALT SALTS	263-064-0	N/A	N/A	0-1%
ALIPHATIC HYDROCARBONS (STODDARD TYPE)	232-489-3	N/A	N/A	15-25%
LIMESTONE CALCIUM CARBONATE	1317-65-3	N/A	N/A	40-70%
HEAVY HYDROTREATED NAPHTHENIC DISTILLATES (PETROLEUM)	64742-53-6	N/A	N/A	5-10%

*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

SECTION 4 – FIRST-AID MEASURES

Inhalation: None.**Skin:** Wash skin thoroughly with soap and water.**Eyes:** Flush with water for 15 minutes. If irritation persists, get medical attention.**Ingestion:** DO NOT INDUCE VOMITING. Contact physician immediately.

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazard: None.**Combustion Products:** None.**Extinguishing Media:** Carbon Dioxide Gas, Dry Chemical, Foam.**Unsuitable Extinguishing Media:** None known.**Protective Equipment:** Wear full firefighting turn-out gear & respiratory protection.**Special Fire Fighting Procedures:** As appropriate for combustibles in area.

GHS SAFETY DATA SHEET

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use recommended personal protective equipment.

Protective Equipment: None.

Emergency Procedures: None.

Environmental Precautions: None.

Methods for Cleaning Up: Sweep or scrape up. If large quantities are exposed to excessive heat, this product may melt. Allow melted material to cool and then scrape up.

SECTION 7 – HANDLING AND STORAGE

Handling

Wash thoroughly after handling.

Storage

Store in a dry/cool place. Store away from incompatible materials.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

This product is not classified as hazardous according to OSHA 1910.1200.

Engineering Controls: A source of running water to flush or wash the eyes and skin in case of contact. Use local exhaust as needed.

Ventilation: Local ventilation is adequate.

Personal Protective Equipment – Respiratory: NIOSH approved respirator. **Skin:** Oil Resistant Gloves. **Eyes:** Safety Glasses/Chemical Goggles.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Cylindrical Crayon/Solid	Flash Point:	400°F	Vapor Pressure:	Not Established
Odor:	Linseed Oil	Specific Gravity:	>1	Flammability:	Not Established
pH:	Not Established	Solubility (H2O):	Water:Insoluble; Fat:Soluble	Flammability Limits:	LEL – Not Established
Melting Point:	150°F	Evaporation Rate:	Not Established		UEL – Not Established
Freezing Point:	Not Established	Vapor Density:	Not Established		
Boiling Point:	Not Established	VOC:	0 g/l		

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Conditions to avoid: High surface area exposure can result in release of heat while product is polymerizing (drying).

Incompatible materials: Oxidizers.

Hazardous decomposition products: Aldehydes (including acrolein) may be produced from atmospheric oxidation (drying).

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxicity

This product is not classified as hazardous according to OSHA 1910.1200.

Likely Routes of Exposure: Inhalation, Eye Contact and Ingestion.

Symptoms and Effect - Inhalation: Irritating fumes may be produced during the products drying process if exposed to large surface area.

Skin Contact: None. **Eye Contact:** May cause mild eye irritation including stinging, watering and redness. **Ingestion:** Possible nausea or diarrhea if large amounts are ingested.

Long-Term Effect: None known.

Pre-Existing Conditions: None known.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: None known.

Persistence & Degradability: None known.

Bioaccumulative Potential: None known.

Mobility in soil: None known.

SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

GHS SAFETY DATA SHEET

SECTION 14 – TRANSPORTATION INFORMATION

D.O.T. (U.S.): Not Regulated.

SECTION 15 – REGULATORY INFORMATION

Precautionary Label Information: None.

Risk Phrases: None.

Safety Phrases: S2-Keep out of reach of children.

SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2025