



SECTION 1 - IDENTIFICATION

Manufacturer: Black Swan Mfg. Co. 4540 W. Thomas St. Chicago, IL 60651-3318 Tel.: 800-252-5796 Fax: 773-227-3705 Web Site : www.blackswanmfg.com E-mail : info@blackswanmfg.com	For any Transportation or Medical Chemical Emergencies call: INFOTRAC (800) 535-5053 OR (352) 323-3500 24 hours per day - 7 days a week
Product Name: Solder Bar, Wiping 40 Tin/60 Lead	Recommended Use: High quality solder for plumbing and joining copper pipes.

SECTION 2 – HAZARD(S) IDENTIFICATION

Labels Signal Word Warning HMIS HEALTH 1 FLAMMABILITY 0 REACTIVITY 0	NFPA HEALTH HAZARD 4 – Deadly 3 – Extreme Danger 2 – Hazardous 1 – Slight Hazardous 0 – Normal Material 1 0 0 0 SPECIFIC HAZARD Oxidizer OX Acid ACID Alkali ALK Corrosive COR Use NO WATER Radioactive FIRE HAZARD Flash Points 4 – Below 73°F 3 – Below 100°F 2 – Above 100°F, Not exceeding 200°F 1 – Above 200°F 0 – Will not burn REACTIVITY 4 – May detonate 3 – Shock and heat may detonate 2 – Violent chemical change 1 – Unstable if heated 0 – Stable	GHS Classification Health Acute Toxicity: Not Established Skin Irritation: Not Established Eye Irritation: Not Established Skin Sensitization: NO Environmental Acute Aquatic Toxicity: Not Established Chronic Aquatic Toxicity: Cat. 1 Physical Carcinogenicity: Cat. 2 Reproductive: Cat. 1A Target Organ Toxicity (single): Cat. 3 narcotic effects Target Organ Toxicity (repeated): Cat. 1 (brain, liver, kidney)
Hazardous Statements H336: May cause drowsiness or dizziness H351: Suspected of causing cancer H360: May damage fertility or the unborn child H372: Causes damage to organs (brain, liver, kidney) through prolonged or repeated exposure H410: Very toxic to aquatic life with long lasting effects	Precautionary Statements P102: Keep out of reach of children P202: Do not handle until all safety precautions have been read and understood P260: Do not breathe dust, fumes, gas, mist, vapors, or spray P264: Wash thoroughly after handling P270: Do not eat, drink or smoke when using this product P271: Use only outdoors or in a well-ventilated area P273: Avoid release to the environment P280: Wear protective gloves, protective clothing, eye & face protection	

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals	CAS#	EINECS#	REACH Pre-registration Number	Approx %
TIN	7440-31-5	N/A	N/A	0-100%
LEAD	7439-92-1	N/A	N/A	0-100%

*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

SECTION 4 – FIRST-AID MEASURES

Inhalation: Move into fresh air. If irritation persists, get medical attention. Skin: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. Eyes: Flush with water for 15 minutes. If irritation persists, get medical attention. Ingestion: Rinse mouth. If irritation persists, get medical attention.

GHS SAFETY DATA SHEET

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazard: During fire, gases hazardous to health may be formed.
Combustion Products: None known.
Extinguishing Media: Dry Chemical Powder, Dry Sand, Water Fog, Carbon Dioxide.
Unsuitable Extinguishing Media: Water, Moist Sand.
Protective Equipment: Self-contained breathing apparatus {(SCBA), MSHA/NIOSH}. Full protective gear.
Special Fire Fighting Procedures: Evacuate enclosed areas, stay upwind. Closed or confined quarters require self-contained breathing apparatus, positive pressure hose masks or airline masks.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Prevent contact with skin or eyes. Personnel cleaning up the spill should wear appropriate personal protective equipment, including respirators if vapor concentrations are high.
Protective Equipment: Respirators and protective clothing.
Emergency Procedures: Evacuate area and keep unnecessary and unprotected personnel from entering the spill area.
Environmental Precautions: Avoid runoff into storm sewers, ditches and waterways.
Methods for Cleaning Up: If large quantities of dust are spilled, remove by vacuuming or wet sweeping to prevent heavy concentrations of airborne dust. Scrap metal can be reclaimed for use.

SECTION 7 – HANDLING AND STORAGE

<u>Handling</u>	<u>Storage</u>
Avoid contact with eyes, skin and clothing. Avoid prolonged breathing of vapor and mist. Use with adequate ventilation. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep products away from heat, sparks, flames and all other sources of ignition.	Store in a cool, dry, well-ventilated area away from incompatible materials. Store in a closed container. Keep away from heat, sparks, open flame and other sources of ignition. Incompatible Materials: Acids, bases and oxidizers.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Hazardous Chemicals</u>	<u>ACGIH-TLV</u>	<u>Exposure Limits</u> <u>ACGIH-STEL</u>	<u>OSHA-PEL</u>
Tin	2mg/m ³	4mg/m ³	2mg/m ³
Lead	.05mg/m ³	N/A	N/A

Engineering Controls: A source of running water to flush or wash the eyes and skin in case of contact.
Ventilation: Use general and local exhaust ventilation to keep airborne concentrations of dust and fume below the TLV.
Personal Protective Equipment – Respiratory: MSHA/NIOSH approved respirators.
Personal Protective Equipment – Skin: Showering should be required before changing to street clothes. Gloves and barrier creams may be necessary to prevent skin sensitization and dermatitis.
Personal Protective Equipment – Eyes: Approved safety glasses or goggles should be worn when working with dusty material.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Silver-gray metal	Flash Point:	Not Established	Vapor Pressure:	Not Established
Odor:	Odorless	Specific Gravity:	Not Established	Flammability:	Not Established
pH:	Not Established	Solubility (H2O):	Not Soluble	Flammability Limits:	LEL - Not Established
Melting Point:	360-460 °F (182.22-237.78°C)	Evaporation Rate:	Not Established		UEL - Not Established
Freezing Point:	Not Established	Vapor Density:	Not Established		
Boiling Point:	Not Established	VOC:	Not Established		

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.
Hazardous polymerization: No dangerous reaction known under conditions of normal use.
Conditions to avoid: Contact with incompatible material.
Incompatible materials: Acids, Chlorine and Strong oxidizing agents.
Hazardous decomposition products: No hazardous decomposition products are known.

GHS SAFETY DATA SHEET

SECTION 11 – TOXICOLOGICAL INFORMATION

Hazardous Chemicals

Tin
Lead

Toxicity

LD₅₀

N/A
N/A

LC₅₀

N/A
N/A

Likely Routes of Exposure: Inhalation.

Symptoms and Effect - Inhalation: Fumes may cause metal fever with flu like symptoms.

Skin Contact: Irritation of the skin and mucous membranes and may result in a benign pneumoconiosis. May cause skin and hair discoloration. **Eye Contact:** None. **Ingestion:** None.

Long-Term Effect: None known.

Pre-Existing Conditions: None known.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: Very toxic to aquatic life with long lasting effects.

Persistence & Degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in soil: No data available.

SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

D.O.T. (U.S.): Not Regulated

SECTION 15 – REGULATORY INFORMATION

Precautionary Label Information: None.

Risk Phrases: None.

Safety Phrases: S2-Keep out of reach of children.

Calif. PRO. 65 – Chemical Warning (California Health and Safety Code #25249.5 ET SEQ). – Warning: This product contains chemicals known to the state of California to cause cancer, birth defects or reproductive harm.

SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2025