



SECTION 1 - IDENTIFICATION

Manufacturer:

Black Swan Mfg. Co.
4540 W. Thomas St.
Chicago, IL 60651-3318
Tel.: 800-252-5796
Fax: 773-227-3705
Web Site : www.blackswanmfg.com
E-mail : info@blackswanmfg.com

For any Transportation or Medical Chemical Emergencies call:

INFOTRAC(800) 535-5053 **OR** (352) 323-3500

24 hours per day - 7 days a week

Product Name: Plumbers Waxy Plug**Recommended Use:** For plugging small leaks on a temporary basis.

SECTION 2 – HAZARD(S) IDENTIFICATION

Labels

None

Signal Word

None

HMIS

HEALTH 0

FLAMMABILITY 1

REACTIVITY 0

NFPA**HEALTH HAZARD**

4 – Deadly
3 – Extreme Danger
2 – Hazardous
1 – Slight Hazardous
0 – Normal Material

SPECIFIC HAZARD

Oxidizer
Acid
Alkali
Corrosive
Use NO WATER
Radioactive

**FIRE HAZARD**

Flash Points
4 – Below 73°F
3 – Below 100°F
2 – Above 100°F, Not exceeding 200°F
1 – Above 200°F
0 – Will not burn

REACTIVITY

4 – May detonate
3 – Shock and heat may detonate
2 – Violent chemical change
1 – Unstable if heated
0 – Stable

GHS Classification**Health**

Acute Toxicity: Not Established
Skin Irritation: Not Established
Eye Irritation: Not Established
Skin Sensitization: NO

Environmental

Acute Aquatic Toxicity: Not Established
Chronic Aquatic Toxicity: Not Established

Physical

None

Hazardous Statements

H303: May be harmful if swallowed

Precautionary Statements

P102 : Keep out of reach of children

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemicals	CAS#	EINECS#	REACH Pre-registration Number	Approx %
HYDROCARBON WAXES, MICROCRYSTALLINE	63231-60-7	N/A	N/A	30-40%
SOLVENT PARAFFIN WAX	8009-03-8	N/A	N/A	30-40%
KAOLIN	1332-58-7	N/A	N/A	15-30%

*Unlisted ingredients are not classified as hazardous according to OSHA 1910.1200.

SECTION 4 – FIRST-AID MEASURES

Inhalation: None.**Skin:** Wash affected area thoroughly with waterless cleaner and/or soap and water. If irritation persists, consult physician.**Eyes:** Flush eyes with large amounts of water for at least 15 minutes, holding eyelids open. Consult a physician if irritation persists.**Ingestion:** If swallowed, give two glasses of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. Consult a physician.

SECTION 5 – FIRE-FIGHTING MEASURES

Fire Hazard: None.**Combustion Products:** None.**Extinguishing Media:** Dry Chemical, Carbon Dioxide, Foam, Water Fog.**Unsuitable Extinguishing Media:** Direct water stream.**Protective Equipment:** Wear a self-contained breathing apparatus.**Special Fire Fighting Procedures:** Evacuate the area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus. Use water to cool exposed surfaces to fire and to protect personnel. Molten material can form flaming droplets if ignited. Use of water on the material above 100°C (212°F) can cause the material to expand with explosive force.

GHS SAFETY DATA SHEET

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions: None.
Protective Equipment: None.
Emergency Procedures: None.
Environmental Precautions: None.
Methods for Cleaning Up: Clean up by scrapping and put in a container for disposal.

SECTION 7 – HANDLING AND STORAGE

Handling
 Keep out of reach of children.

Storage
 Store away from flame, away from heat and away from strong oxidizing agents.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits
 This product is not classified as hazardous according to OSHA 1910.1200.

Engineering Controls: A source of running water to flush or wash the eyes and skin in case of contact. Use local exhaust as needed.
Ventilation: Local ventilation is adequate.
Personal Protective Equipment – Respiratory: None. **Skin:** Gloves. **Eyes:** Safety Glasses.

SECTION 9 – PHYSICAL & CHEMICAL PROPERTIES

Appearance: White to Amber	Flash Point: >360°F	Vapor Pressure: Not Established
Odor: Petroleum	Specific Gravity: 0.705	Flammability: Not Established
pH: Not Established	Solubility (H2O): Negligible	Flammability Limits: LEL – 0.9%
Melting Point: 140-155°F	Evaporation Rate: Not Established	UEL – 7.0%
Freezing Point: Not Established	Vapor Density: >1	
Boiling Point: Not Established	VOC: 0 g/l	

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.
Hazardous polymerization: Will not occur.
Conditions to avoid: Excess heat, direct flame.
Incompatible materials: Strong oxidizers.
Hazardous decomposition products: Upon combustion, Carbon Dioxide, Carbon Monoxide, and other products such as aldehydes and ketones depending on conditions of oxidation.

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxicity
 This product is not classified as hazardous according to OSHA 1910.1200.

Likely Routes of Exposure: Skin Contact and Eye Contact.
Symptoms and Effect - Inhalation: Exposure to fumes, vapors, fumes, or smoke from molten material handled in confined areas can produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals. **Skin Contact:** Molten material can cause severe burns. **Eye Contact:** Exposure to fumes, vapors or smoke from thermally degraded product can cause irritation to eyes. **Ingestion:** Handle with care and DO NOT ingest, or put in mouth.
Long-Term Effect: None known.
Pre-Existing Conditions: None known.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: None known.
Persistence & Degradability: None known.
Bioaccumulative Potential: None known.
Mobility in soil: None known.

GHS SAFETY DATA SHEET

SECTION 13 – DISPOSAL CONSIDERATION

Dispose of product or container in accordance with federal, state or local regulations.

SECTION 14 – TRANSPORTATION INFORMATION

D.O.T. (U.S.): Not Regulated.

SECTION 15 – REGULATORY INFORMATION

Precautionary Label Information: None.

Risk Phrases: None.

Safety Phrases: S2-Keep out of reach of children.

SECTION 16 – OTHER INFORMATION

Information on this form is furnished solely for the purpose of compliance with the Occupational Safety and Health Act and shall not be used for any other purpose. Black Swan Mfg. Co. urges the customers receiving this Material Safety Data Sheet to study it carefully to become aware of the hazards, if any, of the product involved. In the interest of safety, you should notify your employees, agents and contractors of the information on the sheets.

DATE: 01/01/2026